

TECHNICAL DATA SHEET

Exterior Textured PVA



Product:

Last revision:

03/02/2017

We at COSOL Products strive to supply the highest quality of Industrial Paints. Our products offers the highest durability with excellent resistance against the South African elements.

COSOL Textured PVA offers good leveling, coverage and adhesion on clean, and well prepared substrates.

Our Textured PVA Paint is formulated to have a course finished surface with excellent surface hardness.

The color pigment in our Textured PVA Paint have very good lightfast properties.

COSOL Textured PVA is available in a range of standard colors.

COSOL Textured PVA protects and weatherproofs exterior walls.

COSOL Textured PVA paint is recommended for cement substrates in domestic and industrial environments.

COSOL Textured PVA paint is a medium-fast drying product with excellent long lasting properties.

Description:

COSOL Textured PVA paint is a an extremely durable water based textured coating.

The high Acrylic content in our Textured PVA ads to the flexibility to cover hairline cracks, and preventing future cracking.

COSOL Textured PVA paint is an extremely durable water based textured coating.

Please use the correct PPE and safety measures when using this product in an enclosed environment.

Easy to apply, and have a very high Dry film thickness. Compared to our competition.

COSOL Textured PVA contains no added Lead.

Advantages:

Can be used on previously painted surfaces, made from Cement plaster, Concrete, Brickwork, and Gypsum.

Ideal for external walls

Properties:

Appearance:	White before tinted
Color available:	Standard range
Specific gravity:	1,5 - 1,6 approx
Product Viscosity:	Approx 150 KU @ 24degC High Humidity and Low temperatures will affect the product viscosity.
Finish (Dry Film):	Matt, course
<u>Drying Time</u>	(Depending on Temperature & humidity)
To Touch:	Within 30 minutes
To Handle:	Within 60 minutes
To Recoat:	Within 240 minutes
Hard Dry:	Within 24 hours
Vehicle Type:	Modified Acrylic Emulsion
Dry Film Thickness	70 - 100 micron per coat
Packaging size:	5 L, 20 L
Theoretical Spreading rate:	8m ² per Liter, depending on substrate
Application:	Brush, or roller.
Thinning:	Not recommended, Ready to use.
Cleaning:	Water

TECHNICAL DATA SHEET



Textured PVA

Uses:

- * Exterior and Interior walls
- * Complete range of other surfaces provided they have been prepared properly.
- * Where high scrubability is required.

Store in a cool dry space Stirr product well before use. Shelf life is
At least 12 months when stored as directed in undamaged and unopened containers

Health & Safety:

- * Complies with Environmental Specifications
- * Store in a cool dry place
- * Keep away from children
- * Ensure adequate ventilation when using the product
- * Avoid breathing excessive vapors
- * When painting, always wear proper respiratory equipment and protective clothing
- * Avoid contact with eyes. In case of contact with eyes, irrigate thoroughly with water and seek medical advice
- * Avoid contact with skin
- * Wash splashes from skin using a recognized skin cleaner
- * Do not disperse into drains
- * Contains no added lead

NIOEC SP-80-02 Specifications should be followed.

Disclaimer:

We Endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. The Quality Control at COSOL Products ensures that each product that leave our production line is a an exceptional standard, however, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest instructions and safety information.



Cell: 072 935 9749
Office: 016 340 9564
Fax: 016 340 9564
Email: info@cosol.co.za
Website: www.cosol.co.za
Suite 21, Private Bag H 607, Heidelberg 1438

quality coatings and solvents